

In addition to roof space ventilation at high or low level, with an adaptor pack, the UV resistant polypropylene 10K Slate Vent can also be used for soil ventilation or mechanical extraction.

Product features & benefits

- Low profile design to blend with the roof line
- Slate Grey cap blends with most man-made or natural slates
- Designed to avoid any build up of debris inside the vent
- Clearly marked for cutting to various slate sizes
- Prevents entry of birds and large insects
- Adaptor required to convert to soil ventilation or mechanical extraction using Klober 100/100mm flexipipe

Area of application

Suitable for:

- 600mm x 300mm (24" x 12") and 500mm x 250mm (20" x 10") double lap slates
- Man-made or natural slates
- Pitch between 20°- 70°
- High or low level ventilation
- New build or re-roofing situations

Material

UV resistant polypropylene

Colour

Slate grey, matt finish

Product Codes

10K Slate Vent	KG968900
10K Adaptor	KG979100
Flexipipe 100/100mm	KG979900
Adaptor and Flexipipe	KG979200

Dimensions / Weight (per carton)


600mm long x 300mm wide x 60mm deep (excluding downpipe) / 8kg

Packaging

10 pcs per carton

Related products

When used as high level ventilation, this product should be used in conjunction with Klober eaves ventilation products such as Easy-Fit Soffit Strips, Soffit Vents or Fascia Vents.



Installation

The Slate Vent is positioned as standard and a hole is cut in the roofing underlay directly below the vent cap position. The two lower slates are trimmed to allow the pipe to pass through between them and centre nailed in position. The Slate Vent is positioned

through the hole in the slates and centre nailed. NB. if using 500mm x 250mm slates cut away the side sections of the Slate Vent shown by guidelines on the underside. For headlaps in excess of 100mm cut off the front section shown on the underside. Slating is continued as normal.

Regulations and certifications

Complies fully with relevant Building Regulations and British Standards

PERFORMANCE / TECHNICAL DATA

Provides effective vent area 10,000mm²

Vent spacing

5mm opening at 2m centres

10mm opening at 1m centres

TS-00#15-UK-0214. We assume no liability for typing errors.

Klober Ltd

Unit 6F · East Midlands Distribution Centre · Short Lane · Castle Donington · Derbyshire · DE74 2HA
Tel. +44 (0)1332 813 050 · Fax +44 (0)1332 814 033 · info@klober.co.uk · www.klober.co.uk

KLOBER