



Butylon is a double-sided tape for sealing nail penetrations through underlays as well as sealing underlays, air barriers or vapour control layers (AVCL's) to both smooth and rough surfaces. Both internal and external use.

Product features & benefits

- Double-sided tape
- Ideal for creating airtight seals around nail penetrations through underlays/AVCL's or adhering underlays/AVCL's to both smooth & rough surfaces
- Highly durable
- Watertight

Area of application

Suitable for:

- Adhering underlays & vapour control layers/air barriers to smooth & rough surfaces
- Use below tile battens or counterbattens to seal nail penetrations through the underlay
- Both internal & external use

Material

Double-sided butylon-rubber adhesive

Dimensions / Weight (per carton)

20mm x 25m: 3 kg

50mm x 25m: 4.3 kg

Packaging

20mm x 25m: 4 rolls per carton

50mm x 25m: 2 rolls per carton

Product codes

20mm x 25m: KU 0103

50mm x 25m: KU 0104

Related products

Any Klover underlay

Wallint[®] 50 or Wallint[®] solar vapour control layers/air barriers

TECHNICAL DATA

Adhesive	Butylon [®]
Solvent	Solvent free
Installation temperature	> +5°C
Temperature stability	-40°C to + 80°C
UV stability	4 months
Resistance to ageing	It remains permanently elastic & adhesive
Shelf life	2 years at 20°C or less

TS-09#16-UK-0114. We assume no liability for typing errors.

Klover Ltd

Unit 6F · East Midlands Distribution Centre · Short Lane · Castle Donington · Derbyshire · DE74 2HA
Tel. +44 (0)1332 813 050 · Fax +44 (0)1332 814 033 · info@klover.co.uk · www.klover.co.uk