

# Easy-Form® Solar Sealing Collar

Prevents the ingress of water under the roof covering



The Easy-Form® Solar Sealing Collar re-establishes the weather-tightness of the roof covering, which is impaired by the removal of the interlocking joints of the roof tiles for installation of solar hooks. If a roof tile cracks because of high applied load, water can penetrate into the roof structure. Easy-Form® Solar Sealing Collar also helps in this case to protect the roof structure from the ingress of water and snow and to prevent damage caused by water until the next scheduled maintenance.

## Product features

- Protection against rain and fine snow at head interlocking joint
- Can be used with numerous of standard solar hooks
- Can be universally used with all types of roofings
- Self-fixing to dry surfaces with adhesive butyl strip
- Easily mouldable to fit with any profile
- Environmentally friendly, lead-free

## Area of application

- Can be used for roof pitches of 10° & over
- Compatible with almost all concrete and clay tiles as well as roofing slate

## Product details

- Aluminum with full-surface butylon coating and reinforcement layer
- Highly flexible
- Elastic EPDM-collar seal

## Product codes / Colours

- |         |   |
|---------|---|
| KW 0030 | red (-0154), black (-0450), anthracite (-0469)                |
| KW 0045 | red (-0154), black (-0450), anthracite (-0469), brown (-0248) |



## TECHNICAL DATA

Dimensions	450 x 300 mm (KW 0030) 450 x 450 mm (KW 0045)
Roof pitch	> 10°
Resistance	does not rot, is UV- and weather-resistant, resistant to frost, ageing & changes in temperature
Building material group	B2
Water column	watertight
Thickness	approx. 1.2 mm
Temperature resistance	-20°C / +80°C
Installation temperature	+5°C / +40°C
Butyl adhesive	Surface must be dry and dust free
UV-Resistance	UV stable due to metallic upper surface
Compatible solar hooks (w x h)	30 x 5; 35 x 5; 40 x 5; 30 x 6; 35 x 6; 40 x 6 mm
Packaging	20 pieces / carton, 400 pieces / pallet

TS-SL#13-UK-0114. We assume no liability for typing errors.

### Klober Ltd

Unit 6F · East Midlands Distribution Centre · Short Lane · Castle Donington · Derbyshire · DE74 2HA  
Tel. +44 (0)1332 813 050 · Fax +44 (0)1332 814 033 · info@klober.co.uk · www.klober.co.uk

# KLOBER