



Klober's Trapac® Walkway allows work to be carried out more safely on the roof. Available in 4 colours to blend in with the roof, it suits concrete, clay, slate or fibre cement roofs.

Product features & benefits

- Allows work to be carried out on the roof more safely, giving access to large areas of the roof
- 9 lengths available
- Lengths can easily be joined together using Connectors
- Available in 4 colours to blend in with the roof
- Universal for all roof types
- Solid and safe
- Adjustable for roof pitches
- Support brackets are adjustable in height & length for use with different profiles

Area of application

Suitable for:

- Different tile profiles
- Concrete, clay, slate & fibre cement
- Different roof pitches using adjustable support brackets



Dimensions / Weight

Please contact our Sales Office for details.

Regulations

- CE-certified
- DIN EN 516
- DIN 18160 T5C



Material

Walkway

Galvanised steel DX52 D+AZ 150 NA-C, powder coated

Connectors & Support Brackets

Galvanised steel DX51D/S235 JRG2 to EN1461

Fixings for Walkway to Support Bracket

Galvanised steel

Colours

| | | | |
|-----------------------|------|------------------|------|
| Red (RAL 8004) | 9804 | Galvanised | 0370 |
| Dark brown (RAL 8019) | 9819 | Black (RAL 9005) | 9905 |

Packaging

Connectors (to be used when 2 walkways are joined ie. 300cm + 300cm to get a 600cm wide walkway)

1 bag contains 2 connectors, 8 screws, washers and nut bolts

Fixings for Walkway to Support Bracket

1 bag consists of 2 bolts, 2 washers and 2 nuts (1 fixing pack for 1 support bracket)

Support bracket

10 pcs per carton

Product codes

| | | | |
|-------|--------|-------|--------|
| 42cm | KS9130 | 150cm | KS9135 |
| 60cm | KS9131 | 204cm | KS9136 |
| 84cm | KS9132 | 252cm | KS9137 |
| 102cm | KS9133 | 300cm | KS9138 |
| 120cm | KS9134 | | |

| | |
|--|--------|
| Connector | KS9140 |
| Support bracket clay/concrete | KS9120 |
| Support bracket slate/flat/ fibre cement | KS9121 |
| Fixings | KS9141 |

Installation

Walkway up to 102 cm (KS9130 - KS9133) requires 2 support brackets (either KS9120 or KS9121) dependant if fitting with slates or tiles and each support bracket requires 1 pack of fixings KS9141.

Walkways up to 300 cm (KS9134 - KS9138) requires 3 support brackets with 3x KS9141.

Walkway should not exceed edge of Support Bracket by more than 10cm. To fit Walkway to Support Bracket two fixings per Support are required. The Support Brackets allow for 3 degrees of horizontal adjustment.

Profiled Tiles with load-bearing battens: Support Bracket is hung onto load-bearing batten. Additional battens are not required. With large format clay tiles an additional batten may be necessary if the distance between the battens is greater than 37cm.

Flat Tiles: For flat tiles an additional batten is required so that the Support Bracket can be secured through three holes in the metal strip.

Maximum distance between Support Brackets is 90cm.

Klober's installation instructions should be followed closely when fitting this product.

Klober Ltd

Unit 6F · East Midlands Distribution Centre · Short Lane · Castle Donington · Derbyshire · DE74 2HA
Tel. +44 (0)1332 813 050 · Fax +44 (0)1332 814 033 · www.klober.co.uk · info@klober.co.uk