


Permo[®] extreme RS SK²

Bondable underlay for a rainproof subroof



Installation

Klober recommends that the membrane is laid on a 12mm plyboard/OSB then counter-battened. Butylon tape should be laid underneath where the counter battens are due to be fixed, to seal around any nail penetrations.

In accordance with BS5534 the minimum head lap of any membrane needs to be 100mm when laid on a supported roof down to 15°, the 2 adhesive strips will meet, therefore no need for any other adhesives. Below 15° the head lap would need to be 150mm, therefore, a butylon tape would be required to seal the overlaps. Contact Technical for further information.

Permo[®] extreme RS SK² is a tear-resistant underlay. It has double, self-adhesive strips which provide a permanent seal of overlaps and immediate weatherproofing protection against wind, rain and snow. Klober accessories are essential when being laid as key primary barrier. These are especially coordinated with the layer and included in the warranty.

Product features & benefits

- Double self-adhesive strips permit permanent wind and water-proof sealing of overlaps (shear resistance > 300 N tested)
- High-temperature stability at peaks up to 100°C and highly UV-resistant
- Fleece with capillary stop controls the formation of condensation water. Robust PES fleece ensures improved mechanical load capacity, thus facilitating the use on sheathing.

Area of application

Suitable for:

- Minimum roof pitch of 12.5° for profile tiles, 15° for flat tiles and 22.5° for plain tiles
- Meets the requirements as a roof support system with improved raintightness according to ÖNORM
- Can be deemed as a primary barrier as long as covered by UV protected layer eg tiles, slates, etc.
- Is vapour permeable however under BS5250 is classed as a HR underlay so requires ventilation

Material

Glueable two-layered underlay with monolithic TPU coating on extremely tear-resistant PES fleece

Product code / Roll size / Roll weight

KU0171-11 / 50 x 1.5m (75m²) / 18kg

Accessories

- KU0103 / KU0104 Butylon[®] Tape

Certification

- CE certified

TECHNICAL DATA

Weight	approx. 240g/m ²	
Water vapour transmission EN 12572 (s _d value)	0.08 m	
Reaction to fire EN 13501-1, EN 11925-2	E	
Water column, EN 20811	> 4,500 mm	
Resistance to water penetration EN 1928	W1	
Resistance to air penetration	< 0.1 m ³ /m ² h 50 Pa	
Tensile strength longitudinal / transverse EN 12311-1	310N/5 cm	360N/5 cm
Elongation longitudinal / transverse EN 12311-1	45%	55%
Resistance to tearing (nail shank) longitudinal / transverse EN 12310-1	215N	200N
Resistance to temperature	-40°C / +100°C	
UV-resistance* / Natural weathering	4 months	
Temporary roofing	8 weeks	
Driving rain test (TU Berlin)	passed	

*The Underlay can be used to provide temporary weather protection; however an exposed underlay will be subjected to UV light which may lead to premature failure; therefore, the exposure period should be kept to a minimum. An underlay is not a total waterproof barrier and if used as a temporary waterproof covering, some rain penetration may occur. In certain conditions, particularly if there is persistent heavy rainfall combined with subsequent severe freeze/thaw conditions, an underlay should not be exposed for more than a few days. (BBA)

Klober Ltd

Unit 6F · East Midlands Distribution Centre · Short Lane · Castle Donington · Derbyshire · DE74 2HA
Tel. +44 (0)1332 813 050 · Fax +44 (0)1332 814 033 · info@klober.co.uk · www.klober.co.uk

KLOBER

CE