

# Mini Uni-Line® Slate Vent



## Installation

The vent is positioned directly in-line with the slates below, and an inverted T opening is cut within the underlay to accommodate the downpipe. To ensure the integrity of the underlay a Klobber Underlay Seal is strongly recommended. Once the downpipe has been located through the underlay opening, the slate vent is located on and fixed to the slate batten. The slates either side of the vent are laid and trimmed if necessary.

Mini Uni-Line® Slate Vent is a universal In-line Slate Vent that suits most small natural slates.

## Product features & benefits

- In-line design
- Fully wind tunnel tested
- Built in downpipe allows direct ventilation to roof space
- No soil/mechanical adaptor required

## Area of application

Suitable for:

- 400mm x 250mm (16 x 10") and below natural double-lap slates
- High or low level roof space ventilation
- Roof pitches of 22.5° and above
- Small natural and fibre cement slates

## Material

UV resistant Polypropylene

## Colours / Product Codes

Dark Slate KG9631-0403  
Slate Grey KG9631-0429

## Dimensions / Weight (per carton)

450mm long x 300mm wide x 147.5mm deep  
(excluding downpipe) / 7.8kg

## Packaging

10 pcs per carton

## Related products

Uni-Flexipipe KG979900  
Underlay Seal KG973100

## Regulations and certifications

Complies fully with relevant Building Regulations and British Standards.

## PERFORMANCE / TECHNICAL DATA

Provides 6,500mm<sup>2</sup> effective vent area.

Vent spacing

5mm opening at 1.2m centres

10mm opening at 0.6m centres

Airflow resistance

15 litres/sec

30 litres/sec

60 litres/sec

24 Pascals

96 Pascals

384 Pascals

TS-00#20-UK-1017. We assume no liability for typing errors.

Klobber Ltd

Unit 6F · East Midlands Distribution Centre · Short Lane · Castle Donington · Derbyshire · DE74 2HA  
Tel. +44 (0)1332 813 050 · Fax +44 (0)1332 814 033 · info@klobber.co.uk · www.klobber.co.uk

**KLOBBER**