



Easy-Form® plus is a very strong and robust universal flashing that combines flexibility and rigidity in a perfect way. Reinforced with a metal grid it's almost rigid as lead, but still moulds easily to the contours of the roof and is particularly effective at wall connections, dormers and chimneys.

### Product features & benefits

- Perfect match of flexibility and rigidity
- Creating weathertight wall connections
- Bridges gaps up to 5cm
- Highly durable – giving similar life expectancy as for lead or zinc
- Wide range of applications
- Flexible and stretchable material – quicker and easier to install than lead
- Strong adhesive butyl backing is self-fixing to dry surfaces
- Does not suffer from wind uplift

### Area of application

- All abutments at walls, chimneys, rising parts of structures such as dormers, fire walls and other abutments in the roof area
- Universal - suitable for almost all tile, clay & slate profiles
- Suitable for new build or refurbishment

### Material

Creped coated aluminium, PET-foil, PET-fleece, complete coating with metal grid and self-adhesive butyl

### Dimensions /Packaging

250mm x 5m / 5 rolls per/carton, 600m/pallet  
 300mm x 5m / 5 rolls per/carton, 600m/pallet  
 450mm x 5m / 2 rolls per/carton, 400m/pallet

### Product codes

KW 4250-05      250mm x 5m  
 KW 4300-05      300mm x 5m  
 KW 4450-05      450mm x 5m

## TECHNICAL DATA

Roof pitch	>10°
Resistance	does not rot, is weather-resistant, resistant to frost, ageing & changes in temperature
Temperature resistance	-20 °C to 80 °C
Installation temperature	+5 °C to 40 °C
Butyl adhesive	should be applied to suitable surfaces only, which are dry & dust free
UV stability	UV stable due to metallic upper surface
Thickness	approx. 1,7 mm
Water column	watertight
Colours	red (0154), dark brown (0248), anthracite (0469), zinc-grey (0470), black (0450)

TS-05#42-EN-0913. Für Druckfehler wird keine Haftung übernommen. ®Eingetragenes Warenzeichen der Klöber GmbH.