



Pre-formed lead-free flexible
flashings for chimneys and
ventilation pipes

Area of application

Sealing gas flue outlets

Sabetoflex provides the perfect collar and flashing combination for gas flues with diameters ranging from 100-160mm.

Unlike traditional metal collars, up to three of which are needed to cover all pitches, Sabetoflex collars can be adjusted to suit the pitch and can be used just as effectively on flat and green roofs*.

*Please contact our Technical Department for specific installation advice.

Sabetoflex kits come complete with a pre-installed Wakaflex® sealing collar which provides an airtight seal with the roof. This offers a far better solution than standard lightweight metal flashings which provide no overall seal and can be inadequate on low pitches. The Wakaflex® plate is provided with butyl strips around the edge for easy fixing.

Installation

For correct installation, please ensure that there is a gap between the pipe and outlet. This is a mandatory requirement, especially for wood burners.

Operating Temperatures

Gas Flue Outlet (Plastic): up to 100°C

Colours & Sizes

Gas Flue Outlets

100mm | 125mm | 160mm

For roof pitches 7°- 48°



Product	Width	Colour	Code
Gas Burner (M-Flex)	100mm	Red	PSFEX100RE
Gas Burner (M-Flex)	100mm	Anthracite	PSFEX100AN
Gas Burner (M-Flex)	125mm	Red	PSFEX125RE
Gas Burner (M-Flex)	125mm	Anthracite	PSFEX125AN
Gas Burner (M-Flex)	160mm	Red	PSFEX160RE
Gas Burner (M-Flex)	160mm	Anthracite	PSFEX160AN

Related Product

Sabetofix M Glue

Using Sabetofix adhesive makes it possible to install a flashing even in rainy weather.

The process is simple: just apply a thin line of Sabetofix on the butyl tape, and it is then possible to install on a wet surface

- Unlike some other adhesives, once opened Sabetofix can be resealed and used again
- Temperature tolerance is between -30°C and 90°C.
Lowest working condition is 5°C.

Size: 290ml

Code: PACCGL



Contact

Haus Profi
Unit 6F, East Midlands Distribution Centre, Short Lane,
Castle Donington, Derbyshire, DE74 2HA, UK

tel: 0845 600 4427
fax: 01332 813 082

email: info@haus-profi.co.uk
www.roof-flashing.info

 @HausProfiUK