# **KLOBER**

# **Sepa Light**



# A non-breathable alternative to 1F felt.

Sepa Light is a three-layer non-breathable roof underlay for ventilated pitched roofs.

The high-resistance membrane is a strong lightweight alternative to traditional 1F felt, and is the ideal solution when traditional ventilation is preferred.




### Features and benefits

- The high-resistance membrane is a strong lightweight alternative for ventilated pitched roofs.
- Absorbent inner layer as recommended in BS 5250.
- High tensile and nail tear strength.

#### Area of application

- Suitable for use on ventilated pitched roofs.
- Often recommended with fibre cement roof coverings.
- All wind zones with taped headlap.
- Wind zones 1-2 with battened headlap.

(Wind zones shown are for a 345mm batten gauge.)



## Related products

- Underlay Support Tray KP973910
- Permo Tape KU0121-1
- Tacto Tape KU0111
- Over Fascia Vent KP965200 / KP964300
- Roll Out Rafter Tray, all sizes.

#### Approvals and certifications

- CE.
- All products supplied by Klober Ltd are covered by a 10 year guarantee against manufacturing defect.





# **Technical guidance**

Material	Nonwoven spunbonded polypropylene			
Colour	Grey			
Weight g/m² EN 1849-2	120			
<b>Water vapour transmi</b> (SD value) EN 12572	>25m			
Resistance to water penetration EN 1928	W1			
Tensile strength MD/C (N/50mm) EN 12311-				
Nail tear strength MD, (N) EN 12310-1	/CD 120/120			
Elongation MD/CD (%) EN 12311-1	60/60			
Fire rating EN 13501-1 EN 11925-	<b>F</b>			
Resistance to temperat	-40°C to + 80°C			

\*The Underlay can be used to provide temporary weather protection; however an exposed underlay will be subjected to UV light which may lead to premature failure; therefore, the exposure period should be kept to a minimum. An underlay is not a total waterproof barrier and if used as a temporary waterproof covering, some rain penetration may occur. in certain conditions, particularly if there is persistent heavy rainfall combined with subsequent severe freeze/thaw conditions, an underlay should not be exposed for more that a few days. (BBA)

#### **Product information**

Product code	Width m	Length m	m²	Weight Per Roll kg	Pallet quantity
KU979145-1	1	45	45	5.6	42

Klober is certified to ISO 9001:2015 for Quality Management and ISO 14001:2015 for Environmental Management. All Klober products comply fully with all relevant Building Regulations and British Standards.