

Trapac® Tile & Snow Guard



Related products

- Trapac® Safety Hook
- Trapac® Safety Step
- Trapac® Walkway Step

Trapac® Tile & Snow Guard supports are the universal answer for prevention of large and deep profiled tiles and snow falling on pitched roofs. The support brackets are suitable for installation with flat and profiled concrete interlocking tiles. They are lightweight and easy to fit, without the need for an additional support batten. Snow guard grids can be connected together using grid connectors.

Product features & benefits

- Quick and easy to install
- Lightweight and easy to fit without need for an additional support batten
- Suitable for both flat and profiled clay and concrete interlocking tiles
- Galvanised and powder coated
- Prevents large and deep profile tiles from falling

Area of application

Suitable for:

- Clay and concrete interlocking tiles with battens between 24–40mm deep. The complete thickness of the tile and the tile batten must not exceed 57mm.
- New build and refurbishment projects

Material

Galvanised flat steel DX51D-Z275 to EN10142

Colours

Red (RAL 8004)	9804
Dark brown (RAL 8019)	9819
Galvanised	0370
Black (RAL 9005)	9905

Product Code / Packaging

Tile Support Brackets*	KS9220-2
Slate Support Brackets*	KS9221
Grid 3m long	KS9210
Grid Connector	KS9215

* Grid is 3m in length and requires 5 brackets to support. Each joint requires 2 connectors.

Installation

Determine the location of the Tile & Snow Guard Support Brackets, usually within the first or second course of tiles up from the eaves. Lay the tiles to the course the brackets are being fixed. Hook the Support Brackets over the tile and tiling batten and pull down over the batten and the tile. Fix into the tile batten with a 50mm ring shank nail. If the brackets are being installed within a profile tile, the brackets must be installed within the pan of the tile. The Support Brackets are fixed at 600mm centres.

Klober's installation instructions should be followed closely when fitting this product.

Klober Ltd

Unit 6F · East Midlands Distribution Centre · Short Lane · Castle Donington · Derbyshire · DE74 2HA
Tel. +44 (0)1332 813 050 · Fax +44 (0)1332 814 033 · www.klober.co.uk · info@klober.co.uk

KLOBER