



Wakaflex® Uni Outlet is a lead-free, flexible, adhesive sealing collar where flue pipes and soil stacks penetrate the roof

Areas of application

Suitable for:

- ✔ Pitched Roof
- ✔ 18° - 45°

Product features

- ✔ Universal sealing of flue pipes and soil stack penetrations
- ✔ Ease of handling and installation
- ✔ Aesthetically pleasing with a high quality finish
- ✔ Lead-free
- ✔ Long life due to polymer surface of Wakaflex and high quality EPDM material
- ✔ Suitable for concrete, clay tiles and slates



The Wakaflex® Uni Outlet is the ideal solution for sealing penetrations in the roof. The outlet is extremely flexible as it is designed to fit a wide range of outlet diameters. It is also very easy to install and unlike other methods of sealing such as aluminium or lead, if the seal needs to be extended, extra Wakaflex® can simply be added to accommodate it.

Performance

Pitched Roof

18° - 45°

Operating Temperatures

Temperature Range

-40°C up to 100°C (up to 120°C short term/intermittently)

Application Temperature

+5°C up to 40 °C

Recommendation for Application

- Surfaces have to be dust, oil, fat free and dry.
- Be aware that sharp edges can damage the EPDM collar.
- Please ensure that the non-supported gap between tiles and roof penetration is less than 50mm, if greater than 50mm additional support will be needed
- Water sags and standing water have to be avoided.

Installation

Measure the diameter of the roof outlet. Cut the collar horizontally to suit, using the size guide on the collar.

Push the Wakaflex collar over the outlet.

The upper edge of the collar to be laid to the top edge of the tile/slate and then should be covered by the next tile course.

Create a welt at the top edge of the collar. Mould Wakaflex completely into tiles/slates without tension.

When placing the top tiles/slates ensure the welt has adhered to the underside of the tile, this is to create a weather tight seal.

When supporting flue by internal structure ensure that water sags and standing water are avoided.

Full instructions are including in the Wakaflex Uni outlet packs



Material

Base Material

Wakaflex®

Polyisobuthylene(PIB) with aluminium-meshwork and butyl-adhesive tape

Collar Material

EPDM

Dimensions

Wakaflex®

Base Dimension

560mm x 450mm

Collar sizes

25mm,50mm,75mm,100mm,
110mm,125mm

Carton Quantities

10 pieces per carton

120 pieces per pallet

Product codes

Wakaflex Uni Outlet - Grey
PWFUO560GR

Contact

Haus Profi

Unit 6F, East Midlands Distribution Centre, Short Lane,
Castle Donington, Derbyshire, DE74 2HA, UK

tel: 0845 600 4427
fax: 01332 813 082

email: info@haus-profi.co.uk
www.roof-flashing.info



@HausProfiUK

