

# WALLINT 50

## DOP KU0065/EN 13859-1

- |    |                      |   |
|----|----------------------|---|
| 1. | Identification code  | <b>KU65</b>   |
| 2. | Identification name  | <b>Wallint 50</b>   |
| 3. | Uses of the CP       | Vapour control layer  |
| 4. | Manufacturer         | <b>Klöber GmbH</b><br><b>Scharpenberger Str. 72-90</b><br><b>58256 Ennepetal</b><br><b>Germany</b>  |
| 5. | System               | Systeme 3   |
| 6. | Harmonized standard  | EN 13859-1 : 2010   |
| 7. | Notified Body        | Not. No.: 0751<br>FIW e.V. München, Lochhamer Schlag 4, 82166 Gräfelfing<br>respectively<br>Not. No.: 0761<br>MPA, Beethovenstraße 52, 38106 Braunschweig |
| 8. | Declared Performance |   |

ESSENTIAL CHARACTERISTICS	PERFORMANCE	STANDARD	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	E	EN 13501-1	
Resistance to water penetration	W1	EN 1928	
Tensile strength (N/50mm) MD	200 (+/-30)	EN 12311-1	
Tensile strength (N/50mm) CD	160 (+/-30)	EN 12311-1	
Resistance to tearing (N) (nail shank) MD	165 (+/-30)	EN 12311-1	EN 13859-1 : 2010
Resistance to tearing (N) (nail shank) CD	175 (+/-30)	EN 12310-1	
Pliability	-20° C	EN 1109	
Resistance to water penetration after ageing	W1	EN 1928	

The declaration of performance is identified in points 1 and 2 is in conformity with the declared performance in table 8.  
The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Stuart Stockley (Managing Director - Klöber)

# DECLARATION OF PERFORMANCE

